

Dear Customer

the following system

System

Main unit

Speakers

illustrated.

EU

Thank you for purchasing this product.

For optimum performance and safety, please

Please keep this manual for future reference.

Your unit may not look exactly the same as

connecting, operating or adjusting this product.

These operating instructions are applicable to

SC-AKX10

SA-AKX10

SB-AKX10

read these instructions thoroughly before

Panasonic

Operating Instructions

CD Stereo System

Model No. SC-AKX10

1 x FM indoor antenna

1 x AM loop antenna

For the United Kingdom

1 x Antenna plug adaptor

EU

EB GN En

RQTX1089-B

L0110CH0

(N1DYYYY00010)

(K1YZ02000013)

(RSAX0002)

SUPPLIED ACCESSORIES

Please check and identify the supplied accessories

1 x AC mains lead

(K2CZ3YY00005)

(K2CJ2DA00008)

1 x Remote control

2 x Remote control

(N2QAYB000500)

batteries

For Australia

For the United Kingdom

Use numbers indicated in parentheses when asking for replacement parts. (As of January 2010)



These symbols on the products, packaging, and/or accompanying documents mean that used electrical and electronic products and batteries should not be mixed with general household waste. r proper treatment, recovery and

recycling of old products and used batteries, please take them to applicable ollection points, in accordance with your national legislation and the Directives 2002/96/EC and 2006/66/EC.

By disposing of these products and batteries correctly, you will help to save valuable resources and prevent any potential negative effects on human health and the environment which could otherwise arise from inappropriate waste handling. For more information about collection and recycling of old products and batteries

please contact your local municipality, your waste disposal service or the point of sale where you purchased the items. Penalties may be applicable for incorrect disposal of this waste, in accordance with national legislation.

Caution for AC Mains Lead

For United Kingdom

For your safety, please read the following text carefully. This appliance is supplied with a moulded three pin mains plug for your safety and convenience

A 5-ampere fuse is fitted in this plug. Should the fuse need to be replaced please ensure that the replacement fuse has a rating of 5-ampere and that it

s approved by ASTA or BSI to BS1362. Check for the ASTA mark \circledast or the BSI mark \heartsuit on the ody of the fuse.

If the plug contains a removable fuse cover you must ensure that it is refitted when the fuse is replaced. f you lose the fuse cover the plug must not be used until a replacement cover is obtained A replacement fuse cover can be purchased from your

ocal deale CAUTION! IF THE FITTED MOULDED PLUG IS UNSUITABLE

FOR THE SOCKET OUTLET IN YOUR HOME THEN THE FUSE SHOULD BE REMOVED AND THE PLUG CUT OFF AND DISPOSED OF SAFELY. THERE IS A DANGER OF SEVERE ELECTRICAL SHOCK IF THE CUT OFF PLUG IS INSERTED INTO ANY 13-AMPERE SOCKET.

If a new plug is to be fitted please observe the wiring code as stated below

If in any doubt please consult a qualified electrician. IMPORTANT

The wires in this mains lead are coloured in accordance with the following code:

Blue: Neutral, Brown: Live. As these colours may not correspond with the coloured

markings identifying the terminals in your plug, proceed as follows The wire which is coloured Blue must be connected to the terminal which is marked with the letter N or coloured

Black or Blue The wire which is coloured Brown must be connected to the terminal which is marked with the letter L or coloured

Brown or Red. WARNING: DO NOT CONNECT EITHER WIRE TO THE EARTH TERMINAL WHICH IS MARKED WITH THE

LETTER E, BY THE EARTH SYMBOL \pm OR COLOURED GREEN OR GREEN/YELLOW.

THIS PLUG IS NOT WATERPROOF-KEEP DRY

SAFETY PRECAUTIONS

Placement

Set the unit up on an even surface away from direct sunlight, high temperatures, high humidity, and excessive vibration. These conditions can damage the cabinet and other components, thereby shortening the unit's service

Place it at least 15 cm away from wall surfaces to avoid distortion and unwanted acoustical effects. Do not place heavy items on the unit

Voltage

Do not use high voltage power sources. This can overload the unit and cause a fire.

Do not use a DC power source. Check the source carefully when setting the unit up on a ship or other place

where DC is used.

Ensure the AC mains lead is connected correctly and not damaged. Poor connection and lead damage can cause fire or electric shock. Do not pull, bend, or place heavy tems on the lead.

Do not handle the plug with wet hands. This can cause

Before use ove the connector cover

Cd

How to replace the fuse The location of the fuse differ according to the type of AC

nains plug (figures A and B). Confirm the AC mains plug fitted and follow the instructions below Illustrations may differ from actual AC mains plug.

For business users in the Europear

If you wish to discard electrical and

[Information on Disposal in other

These symbols are only valid in the

European Union. If you wish to discard

these items, please contact your local

Note for the battery symbol (bottom

two symbol examples): This symbol might be used in combination

with a chemical symbol. In this case it

Directive for the chemical involved

complies with the requirement set by the


authorities or dealer and ask for the

correct method of disposal.


electronic equipment, please contact your dealer or supplier for further information.

Countries outside the European Union

1. Open the fuse cover with a screwdriver



2. Replace the fuse and close or attach the fuse cover



Do not let metal objects fall inside the unit. This can

Do not let liquids get into the unit. This can cause

disconnect the unit from the power supply and contact

cause electric shock or malfunction.

NOTE on MP3

20 sessions

the unit.

CAUTION

- played
- you recorded them

remote control.

remote control operating mode to "REMOTE 2". The main unit and remote control must be set to the

same mode

AC mains lead protection Grasp the plug firmly when unplugging the lead. Pulling

the AC mains lead can cause electric shock. electric shock.

IPPING OR SPLASHING AND THAT CLIMATES.

ARE NO USER SERVICEABLE PARTS INSIDE. REFER SERVICING TO QUALIFIED SERVICE PERSONNEL.

CAUTION!

- DO NOT INSTALL OR PLACE THIS UNIT IN A BOOKCASE, BUILT-IN CABINET OR IN ANOTHER CONFINED SPACE. ENSURE THE UNIT IS WELL VENTILATED. TO PREVENT RISK OF ELECTRIC SHOCK OR FIRE HAZARD DUE TO OVERHEATING, ENSURE THAT CURTAINS AND ANY OTHER MATERIALS DO NOT OBSTRUCT THE VENTILATION VENTS.
- DO NOT OBSTRUCT THE UNIT'S VENTILATION OPENINGS WITH NEWSPAPERS, TABLECLOTHS, CURTAINS, AND SIMILAR ITEMS.
- DO NOT PLACE SOURCES OF NAKED FLAMES, SUCH AS LIGHTED CANDLES, ON THE UNIT.
- **DISPOSE OF BATTERIES IN AN** ENVIRONMENTALLY FRIENDLY MANNER.



application at www.panasonic.co.uk.

Most major credit and debit cards accepted.

ここを開くと不可視レーち ビームを見たり、触れたり

product and the mobile telephone.

Sales and Support Information

Direct Sales at Panasonic UK

For customers: 0844 844 3856

01 289 8333

holidavs).

The socket outlet shall be installed near the equipment

The mains plug of the power supply cord shall remain

To completely disconnect this apparatus from the AC

This product may receive radio interference caused

by mobile telephones during use. If such interference

THIS UNIT IS INTENDED FOR USE IN MODERATE

For the United Kingdom and Republic of Ireland

Customer Care Centre • For customers within the UK: 0844 844 3852

For customers within the Republic of Ireland:

Order accessory and consumable items for your

product with ease and confidence by phoning our

Customer Care Centre Monday-Thursday 9:00am-

5:30pm, Friday 9:30am-5:30pm (Excluding public

Or go on line through our Internet Accessory ordering

Visit our website for product information

E-mail: <u>customer.care@panasonic.co.uk</u>

is apparent, please increase separation between the

Mains, disconnect the power supply cord plug from AC

Inside of product

and easily accessible

readily operable

receptacle.

on our website for further details. Interested in purchasing an extended guarantee? Please call 0870 240 6284 or visit our website www.panasonic.co.uk/guarantee.

ack of produc

"EB" on the packaging indicates the United Kingdom.

Pursuant to at the directive 2004/108/EC, article 9(2)

Panasonic Corporation

Panasonic Testing Centre

Web Site: http://panasonic.net

Panasonic Marketing Europe GmbH

Winsbergring 15, 22525 Hamburg, Germany

CAUTION!

THIS PRODUCT UTILIZES A LASER. USE OF CONTROLS OR ADJUSTMENTS OR PERFORMANCE OF PROCEDURES OTHER THAN THOSE SPECIFIED HEREIN MAY RESULT IN HAZARDOUS RADIATION EXPOSURE DO NOT OPEN COVERS AND DO NOT REPAIR YOURSELF. REFER SERVICING TO QUALIFIED PERSONNEL.

WARNING:

- TO REDUCE THE RISK OF FIRE, ELECTRIC SHOCK OR PRODUCT DAMAGE, DO NOT EXPOSE THIS APPARATUS TO RAIN.
- NO OBJECTS FILLED WITH LIQUIDS, SUCH AS VASES, SHALL BE PLACED ON THE APPARATUS. USE ONLY THE RECOMMENDED ACCESSORIES.
- DO NOT REMOVE THE COVER (OR BACK): THERE

Do not spray insecticides onto or into the unit. They contain flammable gases which can ignite if sprayed into the unit.

Service

vour dealer.

Foreign matter

Do not attempt to repair this unit by yourself. If sound is interrupted, indicators fail to light, smoke appears, or any other problem that is not covered in these instructions occurs, disconnect the AC mains lead and contact your dealer or an authorised service centre. Electric shock or damage to the unit can occur if the unit is repaired, disassembled or reconstructed by unqualified persons. Extend operating life by disconnecting the unit from the power source if it is not to be used for a long time.

electric shock or malfunction. If this occurs, immediately

PLACEMENT OF SPEAKERS



Caution

Speakers are designed identically so that no left or right channel orientation is necessary. You cannot take the front net off the speakers


Use only the supplied speakers.

The combination of the main unit and speakers provide the best sound. Using other speakers can damage the unit and sound quality will be negatively affected.

- Keep your speakers at least 10mm away from the system for proper ventilation.
- These speakers do not have magnetic shielding. Do not place them near televisions, personal computers or other devices easily influenced by magnetism.
- You can damage your speakers and shorten their useful life if you play sound at high levels over extended periods.
- Reduce the volume in the following cases to avoid damage.
- When playing distorted sound. When adjusting the sound quality

Use the speakers only with the recommended system. Failure to do so can damage the amplifier and speakers, and can cause fire. Consult a qualified service person if damage occurs or if a sudden change in performance is apparent Do not attach these speakers to walls or ceilings.

PREPARING THE REMOTE CONTROL



nsert so the poles (+ and -) match those in the remote

obstacles, at a maximum range of 7 m directly in front of

Aim at the remote control signal sensor 9, avoiding

Note on using the remote control Do not mix old and new batteries

- Do not use different types of batteries at the same time Do not take apart or short circuit the batteries.
- · Do not attempt to recharge alkaline or manganese
- batteries. · Do not use batteries if the covering has been peeled off
- Do not heat or expose to flame. · Do not leave the battery(ies) in an automobile exposed
- to direct sunlight for a long period of time with doors and windows closed. Mishandling of batteries in the remote control can caus
- electrolyte leakage, which may cause a fire. Remove the batteries if the remote control is not going to be used for a long period of time. Store in a cool, dar place

Danger of explosion if battery is incorrectly replaced. Replace only with the same or equivalent type recommended by the manufacturer. Dispose of used batteries according to the manufacturer's instructions

NOTE about using a DualDisc

Use alkaline or manganese batteries.

The digital audio content side of a DualDisc does not meet • This unit can access up to 99 tracks. the technical specifications of the Compact Disc Digital Audio (CD-DA) format so playback may not be possible

- Files are treated as tracks and folders are treated as • This unit can access up to 999 tracks, 255 albums and
- Disc must conform to ISO9660 level 1 or 2 (except for
- extended formats). To play in a certain order, prefix the folder and file names with 3-digits numbers in the order you want to play them.
- Limitations on MP3 play If you have recorded MP3 on the same disc as CD-DA,
- only the format recorded in the first session can be
- Some MP3s may not be played due to the condition of the disc or recording • Recordings will not necessarily be played in the order

NOTE on CDs

- This unit can play MP3 files and CD-DA format audio
- CD-R/RW that have been finalised. • It may not be able to play some CD-R/RW due to the
- condition of the recording Do not use irregularly shaped disc. Do not use disc with labels and stickers that are coming
- off or with adhesive exuding from under labels and stickers.
- · Do not attach extra labels or stickers on the disc Do not write anything on the disc

NOTE on USB

Compatible devices Devices which are defined as USB mass storage class: USB devices that support bulk only transfer.
USB devices that support USB 2.0 full speed.

- Supported format
- Folders are defined as album • Files are defined as track.
- Track must have the extension ".mp3" or ".MP3".
- CBI (Control/Bulk/Interrupt) is not supported. • A device using NTFS file system is not supported.
- [Only FAT 12/16/32 (File Allocation Table 12/16/32) file system is supported.]
 Depending on the sector size, some files may not work.
- Maximum album: 255 albums Maximum track: 2500 tracks
- Maximum track in one album: 999 tracks

MAINTENANCE

If the surfaces are dirty

To clean this unit, wipe with a soft, dry cloth.

 Never use alcohol, paint thinner or benzine to clean this unit. Before using chemically treated cloth, read the instructions that came with the cloth carefully.

AVOID INTERFERING WITH OTHER PANASONIC EQUIPMENT


- Other Panasonic audio or video equipment may start functioning when you operate the unit using the supplied You can operate this unit in another mode by setting the
- Press and hold [AUX] 5 on the main unit and [2] 20 until the main unit's display shows "REMOTE 2".

2 Press and hold [OK] 36 and [2] 20 for at least 2

seconds. To change the mode back to "REMOTE 1", repeat steps 1 and 2 by replacing [2] with [1].

MAKING THE CONNECTIONS

Connect the AC mains lead only after all the other connections have been made



CONNECTING TO OTHER EXTERNAL UNIT

You can connect to an analogue player with a built-in phone equaliser.

- Press [AUX] 5 to select "AUX".
- f 2 Play the external unit. (See the external unit's
- instruction manual.)
- All peripheral components and cables are sold
- separately. When units other than those described above are to be
- connected, please consult your audio dealer. Sound distortion may occur when you use an adaptor
- other than the one supplied.

You can select the sound input level of your external unit. You are recommended to set the input level as below: NORMAL : For connection to TV, VCR, DVD Player

- HIGH : For connection to digital audio player such as MP3 player Press [INPUT LEVEL] 38 to select your desired
- HIGH ↔ NORMAL

Note

Level adjustment

• If there is high sound distortion when level "HIGH" is selected, the unit will automatically switch to "NORMAL". • You can also manually select "NORMAL" if there is sound distortion.

DISCS

Playing discs

Press [▲, OPEN/CLOSE] 16 on the main unit to open the tray 17 The unit turns on, load a disc with the label facing up. Press [A, OPEN/CLOSE] 16 again to close the trav [2 Press [►/II, CD] 13 to start play. Stop Press [I] 4 (stop) during play. playback

This unit supports ver. 1.0 and 1.1 ID3 tags.

information about the track.

may be differently displayed.

Program play

2 Press [PROGRAM] 22.

2 Press [PROGRAM] 22.

5 Press [OK] 36

digits

diaits

Cancel

program

program

Replay the

Add to the

program

Check

elect

rogran

ontents

Clear the last

rogrammed

Repeat play

CD MP3

Clear all

acks

Note

tray 17.

'PGM" appears

desired track.

(CD)

· ID3 is a tag embedded in MP3 track to provide

This function allows you to program up to 24 tracks.

1 Press [►/II, CD] 13 and then [■] 4 (stop).

3 Press the numeric buttons 20 to select your

Repeat this step to program other tracks.

1 Press [►/II, CD] 13 and then [■] 4 (stop).

3 Press [▲/▼, ALBUM] 36 to select your desired

4 Press [**>>**/**>**|] 11 once and then the numeric

buttons 20 to select your desired track.

Repeat steps 3 to 5 to program other tracks.

For two-digit track, press [≥ 10] 20 once then the two

For three-digit track, press [\geq 10] 20 twice then the three

Press [PROGRAM] 22 in the stop

In the stop mode, press [>>/>>I] 11

Repeat steps 3 to 5 in the stop mode

Press [I

PGM" is displayed in the stop mode.

Fo check while programming, press

The track number and program order

[PROGRAM] 22 twice after "PGM

appears, then press [I

The program order is displayed

Press [DEL] 21 in the stop mode.

"CLR ALL" is displayed. Within 5

seconds, press the button again to

followed by the album number and

Press [**II**] 4 (clear) in the stop mode

Press [PROGRAM] 22 then

and then repeat step 3

6 Press [►/II, CD] 13 to start play.

node

(CD)

MP3

[►/II, CD] 13

are displayed.

rack number.

clear all tracks.

The program memory is cleared when you open the disc

(MP3)

4 Press [►/II, CD] 13 to start play.

Titles containing text data that the unit does not support

Pause Press [►/II, CD] 13 during play. play Press again to resume play. Skip MP3 album Press [▲/▼, ALBUM] 36 to select the desired album during play or when in stop mode This function does not work during RANDOM mode. Skip tracks During play Press [I [TRACK] 14 to skip to your desired track. While in stop mode Press [I by [►/II, CD] 13 to skip and play your desired track Alternatively, turn [TRACK] 14 to skip and play your desired track. • During random play (→ see "Play Mode function"), you cannot skip to tracks which have been played. You cannot use [TRACK] 14 to skip track during random play. During 1-ALBUM and 1-ALBUM RANDOM mode, track skipping can only be done within the current album. Search CD through tracks Press and hold [I during play or pause to search. During program play, or random play (→ see "Play Mode function"), you can

search only within the track

Diss Made from the

Play Mode function				
CD MP3 Press [PLAY MODE] 32 to select the desired mode.				
1-TRACK ^{1-TR}	Play one selected track on the disc. Press the numeric buttons 20 to select the track. Play starts from the selected track.			
1-ALBUM ^{1-ALB}	MP3 Play one selected album on the disc. Press [▲/▼, ALBUM] is to select the album.			
RANDOM RND	Play a disc randomly.			
1- ALBUM RANDOM 1-ALB RND	MP3 Play all tracks in one selected album randomly. Press [▲/▼, ALBUM] 36 to select the album.			

When playback ends

The current play mode will be retained in memory until it is changed even if the unit is turned off.

• You cannot use program mode together with "Play Mode function" The play mode setting is cleared when you open the disc tray 17

Checking the track information


You can repeat program play or other selected play mode You can view the information of the current track from the Press [REPEAT] 33 "ON REPEAT" and """ are displayed. display pane Press [DISPLAY] 24 repeatedly during play or pause To cancel Press [REPEAT] 33 again. CD "OFF REPEAT" is displayed and """ is cleared. Elapsed play time + Remaining play time Note MP3 You can use repeat mode with "Program play" and "Play Elapsed play time - Remaining play time Mode function' MP3 Press [MP3 INFO] 37 repeatedly during play or pause.

Tag (Album) \rightarrow Tag (Track) \rightarrow Tag (Artist) Elapsed play time

USB		
MP3 The USB connectivity enables you to connect and play MP3 tracks from USB mass storage class. Typically, USB memory devices (bulk only transfer).	Stop playback	Press [■] ④ (stop) during play. "RESUME" is displayed. The position is memorised. Press [▶/II, USB] ⑦ to resume play. Press [■] ④ (stop) again to clear the position.
Playback	Pause play, Skip tracks	These functions have similar operation as described in "Playing discs".
1 Reduce the volume 3 and connect the USB mass storage device to the USB port 8 .	or Skip album	
2 Press [►/II, USB] 7 to start play.	Note: When you connect your digital audio player to the USB port, it charges all the time except in standby mode.	

MAIN UNIT

Standby/on switch [U/I] 2 Press to switch the unit from on to standby mode or vice versa. In standby mode, the unit is still consuming a small amount of power



AM allocation setting

above steps.

Automatic presetting

Preparation

CURRENT

LOWEST

10 kHz steps

This system can also receive AM broadcasts allocated in

After a few seconds the display changes to a flashing

the button. To return to the original step, repeat the

• When the minimum frequency changes, release

• After changing the setting, previously preset

1 Press [PLAY MODE] 32 repeatedly to select either

Tuning begins from the current

Tuning begins from the lowest

To change the step from 9 kHz to 10 kHz

2 Continue to hold down [FM/AM] 15.

frequency will be cleared.

30 FM and 15 AM stations can be preset.

Press [FM/AM] 15 to select "FM" or "AM".

requency.

frequency.

30 FM and 15 AM stations can be preset

Press [FM/AM] 15 to select "FM" or "AM".

2 Press [AUTO PRESET] 25 to start presetting.

The tuner presets all the stations it can receive into the

channels in ascending order. When finished, the last

"CURRENT" or "LOWEST"

station memorised is tuned in.

Manual presetting

required station

3 Press [PROGRAM] 22.

Preparation

OR

1 Press and hold [FM/AM] 15 on the main unit.

display of the current minimum frequency.

RADIO

Manual tuning

1 Press [FM/AM] 15 to select "FM" or "AM".

2 Press [TUNE MODE] 26 to select "MANUAL".

3 Press [I<</ > frequency of the required station. "ST" is displayed when a stereo FM broadcast is being received

To tune automatically

once again.

Press and hold [I frequency starts changing rapidly. The unit begins auto tuning, stopping when it finds a station. Auto tuning may be interrupted when there is excessive

interference To cancel auto tuning, press [I

To improve the sound quality

When "FM" is selected Press [FM MODE] 39 to display "MONO".

To cancel

Press [FM MODE] 39 again until "MONO" disappears. MONO is also cancelled if the frequency is changed. Turn off "MONO" for normal listening.

When "AM" is selected Press and hold [TUNE MODE] 26. Each time you press the button: BP2 ↔ BP1

For the United Kingdom

RDS broadcasting

This unit can display the text data transmitted by the radio data system (RDS) available in some areas If the station you are listening to is transmitting RDS signals, "RDS" will light up on the display. Press [DISPLAY] 24 to display:

Station name _ Program Type _ Frequency

Program type displays				
NEWS	VARIED	FINANCE	COUNTRY	
AFFAIRS	POP M BOCK M	CHILDREN SOCIAL A	NATIONAL OLDIES	
SPORT	M-O-R- M *	RELIGION	FOLK M	
EDUCATE	LIGHT M	PHONE IN	DOCUMENT	
DRAMA	CLASSICS	TRAVEL	TEST	
CULTURE	OTHER M	LEISURE	ALARM	
SCIENCE	WEATHER	JAZZ		

RDS displays may not be available if reception is poor.

4 Press the numeric buttons 20 to select a channel. The station occupying a channel is erased if another station is preset to that channel. 5 Repeat steps 2 to 4 to preset more stations.

1 Press [TUNE MODE] 26 to select "MANUAL".

2 Press [I--/--] / [--/---] 11 to tune to the

Selecting a preset station

Press the numeric buttons ② to select a channel. For channels 10 to 30 press [≥10] ②, then the two digits.

Press [TUNE MODE] 26 to select "PRESET".

2 Press [**I4**/**4**] / [**>**/**>**] 11 to select the

Setting the clock This is a 24-hour clock.

Displaying the clock standby mode.

Sleep timer

after the set time Press [SLEEP] 29 to select your desired time.

To cancel Press [SLEEP] 29 to select "OFF"

The play and sleep timer can be used together The sleep timer always has priority. Be sure not to overlap timer settings.


Play timer

ou up.

Press [PRESET EQ] desired setting.				
HEAVY	Adds pund			
CLEAR	Clarifies h			
SOFT	For backg			
VOCAL	Adds glos:			
FLAT	No effect			

desired setting.

REMOTE CONTROL



CLOCK AND TIMER

Press [CLOCK/TIMER] 28 to select "CLOCK". Each time you press the button CLOCK → ④ PLAY

Criginal display

2 <u>Within 8 seconds or so</u>

Press [▲/▼] 36 to set the time. **3** Press [OK] 36 to finish setting the time.

- Press [CLOCK/TIMER] 28 once when the unit is on or in

The time is displayed for a few seconds.

Reset the clock regularly to maintain accuracy.

This function enables you to turn off the unit automatically

Changing the remaining time

Press [SLEEP] 29 to show the remaining time and press SLEEP] 29 again to select your desired time.

You can set the timer to come on at a certain time to wake

Turn the unit on and set the clock.

SOUND EFFECTS

Changing the sound quality: Preset EQ

ESET EQ] 35 repeatedly to select your etting.		
Adds punch to rock		
Clarifies higher frequencies		
For background music		
Adds gloss to vocal		

Changing the sound quality: Manual EQ

1 Press [MANUAL EQ] 10 repeatedly to select your

- BASS ↔ TREBLE
- **2** Press [**III**] / [►►/►►I] **1** to adjust the level.

• The level of the pitch is between -4 to +4. The changes you make are stored and automatically recalled the next time you select "MANUAL EQ".

IAUTO OFF1 30

- This auto off function allows you to turr off the unit in **disc** or **USB** mode only
- after left unused for 10 minutes Press the button to activate the
- function.
- Press the button again to cancel The setting is maintained even if the unit is turned off.
- [MUTE] 31 To mute the sound.
- Press the button to activate the
- function. Press the button again or adjust the
- volume to cancel

DIMMER] 19 o dim the display panel.

- Press the button to activate the function
- Press the button again to cancel

Prepare the music source you want to listen to; disc,

radio, USB, or other external unit, and set the volume 3

Press [CLOCK/TIMER] 28 repeatedly to select play

CLOCK ----- O PLAY

Criginal display

Press [▲/▼] 36 to set the starting time.

4 Repeat steps 2 and 3 to set the finishing time.

The unit must be turned off for the timer to operate.

Repeat steps 1 to 4 and 6 (\Rightarrow see above).

) Press [@ PLAY] 27 to clear the timer

ndicator from the display.

2) Make changes to the source or

Press [CLOCK/TIMER] 28 repeatedly to

Press [@ PLAY] 27 to clear the timer

3) Perform steps 5 and 6

indicator from the display.

The timer comes on at the set time every day if the timer

• The unit must be in the standby mode for the timer to

functioning, the finish time setting will not be activated

Enhancing the stereo sound: Surround sound

Enables you to add natural width and depth to the stereo

Press [SURROUND] 34 to display "

If interference in FM stereo reception increases, cancel

Changing the sound quality: RE-MASTER

This feature reproduces the frequencies lost during

Press [SURROUND] 34 again to clear "

• If you turn the unit off and on again while a timer is

The play timer will start at the preset time, with the

volume increasing gradually to preset level.

(→ see above).

5 Press [⁽²⁾ PLAY] ^[27] to turn on the timer.

volume

select @ PLAY.

6 Press [⁽¹⁾] 18 to turn off the unit.

Each time you press the button:

2 Within 8 seconds or so

3 Press [OK] 36 to confirm.

To activate the timer

Change the

Change the

source or

Check the

settings

Cancel

is on.

sound.

To activate

To cancel

indicator.

MP3

the surround-sound effect.

function.

volume

settings

[◀/▶] ³⁶ These buttons have the exact same functions as those of [Idd/dd]/ ____, ALBUM] 12

These buttons have the exact same functions as those of [▲/▼, ALBUM] 36

- Distorted sound or noise is heard. The stereo indicator flickers or does not light.
- Use an optional FM outdoor antenna. The antenna should be installed by a competent technician
- A beat sound is heard.
- Turn the television off or move it away from the unit Switch to either BP 1 or BP 2 when in AM tuner mode.
- A low hum is heard during AM broadcast
- Separate the antenna from other cables and cords

Memory reset (Initialisation)

When the following situations occur, refer to the instructions below to reset the memory There is no response when buttons are pressed You want to clear and reset the memory contents

To reset memory

Disconnect the AC mains lead.

(Wait at least 3 minutes before proceeding to step 2.)

2 While pressing and holding down [0/1] 2, reconnect the AC mains lead.

All the settings are returned to the factory preset. You will need to reset the memory items.

SPECIFICATIONS

Amplifier section

RMS Output power stereo mode

Front Ch (both channels driven) 125 W per channel (4 Ω), 1 kHz, 10% THD Total RMS stereo mode powe 250 W

FM/AM tuner, terminals section

FM 30 stations Preset station

Frequency Modulation (FM)

Frequency range 87.50 MHz to 108.00 MHz (50 kHz step) Antenna terminals 75 Ω (unbalanced) Speaker unit(s Amplitude Modulation (AM)

Frequency range 522 kHz to 1629 kHz (9 kHz step) Impedance 520 kHz to 1630 kHz (10 kHz step) Output sound pressure

Aux input RCA pin jack Frequency range

Disc section

Disc played (8 cm or 12 cm) (1) CD-Audio (CD-DA)			
(2) CD-R/RW (CD-DA, MP3* formatted disc) (3) MP3*		General	
* MPEG-1 Layer 3		Power supply	
Pick up		Power consumption	
Wavelength	785 nm (CD)	Dimensions (WxHxD)	25
Laser power	CLASS 1 (CD)	Mass	
Audio output (Disc)		Operating temperature ran	ige
Number of channels	2 (FL, FR)	Operating humidity range	

Number of channels FL = Front left channel FR = Front right channel

recording (original soundtrack) to give you a sound closer to the original. Press [RE-MASTER] 23 repeatedly to select either "ON RE-MASTER" or "OFF RE-MASTER".

Enjoying the bass: D.BASS

Press [D.BASS] 6 repeatedly to select either "ON D.BASS" or "OFF D.BASS".

TROUBLESHOOTING GUIDE

When the unit is in standby mode, the display lights

Press and hold [I] 4 on the main unit to select "NO

No response when remote control buttons are

Check that the batteries are installed correctly.

"humming" sound can be heard during play.

You have not inserted the disc correctly; insert it

• Replace the disc if it is scratched, warped, or non-

Condensation has formed: Wait 1 to 2 hours for it to

The total number of tracks displayed is incorrect.

You have inserted a disc the unit cannot play; insert

You have inserted a disc that has not been finalised or

An AC mains lead or fluorescent light is near the unit.

Keep other appliances and cords away from the unit

Common problems

DEMO".

Discs

correctly.

standard.

evaporate

one it can.

Radio

The disc cannot be read

completely formatted

Distorted sound is heard.

pressed

up and changes continuously.

Distorted sound or no sound

using the unit in a hot environment.

Incorrect display or play will not start.

Disc may be dirty. Wipe it clean.

• Turn the volume up.

Before requesting service, make the following checks. If you are in doubt about some of the check points, or if the solutions indicated do not solve the problem, consult your dealer for instructions

USB

- The USB drive or its contents cannot be read. The USB drive format or its contents is/are not
- npatible with the system
- The USB host function of this product may not work with some USB devices.
- USB devices with storage capacity of more than 8 gigabytes may not work in some instances.
- Slow operation of the USB device Large file size or high memory USB flash drive takes longer time to read.
- Turn off the unit, determine and correct the cause, then turn the unit on again. It may be caused by straining or the speakers through excessive volume or power, and Unit displays

"NO PLAY"

- Check the content • Only MP3 format files can be played.
- If there are more than 255 albums or folders (audio and non-audio), some of the MP3 files in these albums may not be read and played. Transfer these music albums to another USB. Alternatively, reformat the USB device and save these music albums prior to saving the other non-audio folders.

"F61

- Check and correct the speaker cords connection. If this does not fix the problem, consult the dealer. • Disconnect the USB device. Turn the unit off and then
- turn back on
- "ERROR'
- Incorrect operation performed. Read the instructions and try again
- "NOT MP3/ERROR1"

USB section

USB Standard

USB port power

Speaker section

Dimensions (WxHxD)

spectrum analyzer.

Power consumption in standby mode:

1) Specifications are subject to change without notice. Mass and dimensions are approximate.

2) Total harmonic distortion is measured by the digital

Type

Mass

Woofe

Tweeter

Media file format support

USB device file system

USB 2.0 full speed

FAT 12, FAT 16, FAT 32

2 way, 2 speaker system (Bass reflex

MP3 (*.mp3)

500 mA (Max

16 cm cone type

6 cm cone type

85 dB/W (1 m

34 Hz to 22 kHz (-16 dB) 41 Hz to 20 kHz (-10 dB)

AC 220 to 240 V, 50 Hz

250 mm x 336 mm x 245 mm

0.3 W (approximate)

35% to 80% RH (no condensation)

220 mm x 332 mm x 186 mm

4Ω

2.6 kg

62 V

3 k

0°C to +40°C

USB Port

AM 15 stations

- An unsupported MP3 format is being played. The unit will skip that track and play the next one "VBR-
- The unit cannot display the remaining play time for variable bit rate (VBR) tracks.

---- - - - - - " appears on the display panel 1 3 Release [U/I] 2.